

FLASHLINK® MINI PDF IN- TRANSIT LOGGER



- Compact, single-use temperature logger
 - Shadow Log® guarantees trip data
 - No software required for download
- Build-in USB connector, no special reading device needed
- On-board software automatically creates PDF and CSV reports in °F and °C
 - View reports on a PC or tablet
- Recorded data automatically scaled to graph
 - GMT/UTC: 0

Model	31010
Sample Rate	10 Min
Data Capacity	12,288 data points
Trip Duration	85 Days
Temperature Scale	°F/°C



TEMPERATURE LOGGERS

www.hellagro.gr



FLASHLINK® MINI PDF IN- TRANSIT LOGGER



Measurement Range	-40°F to 140°F (-40°C TO 60°C)
Accuracy	±1.0°F from -4°F to 14°F (±0.5°C from -20°C to -10°C) ±0.6°F from 14°F to 50°F (±0.3°C from -10°C to 10°C) ±1.0°F from 50°F to 77°F (±0.5°C from 10°C to 25°C) ±1.8°F if < -4°F or > 77°F (±1.0°C if < -20°C or > 25°C)
Data Download Time	5 seconds typical
Factory Programmable Alarms	High & Low levels over entire range
Delay Start	30 minutes
Battery	Coin Cell Battery
Dimensions	1.858in x 3.071in x 0.402in (47.2mm x 78mm x 10.2mm)
Weight	0.854 oz. (24.2 grams)
Shelf Life	18 Months
Certification	RTCA/DO-160G Sect 21.5, CE Mark, Calibration traceable to NIST, RoHS Compliant
Display	Green and Red LED
Waterproof Rating	IP54 with silicone cap
Storage Conditions	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation
System Requirements	Windows PC with current operating system Adobe Reader
Download Requirements	Direct USB connection to PC, tablet or printer

